

|| PRICE LIST 2023 ||

An obvious choice for excavators

in the weight class 0-10 tons



Narrow design

CompactTilt has been developed for working in narrow gutters and is equipped with compactTilt's patented motor a cylinder-free product. It ensures:

- No stamps that can "get stuck"
- Safe view of the work area from the cab
- Dig in narrow trenches and avoid unnecessary soil movement
- Easier access to the work zone which consists of many supplies – eg city zones

WITH CYLINDERS



WITHOUT CYLINDERS



AVERAGE SIZE
ON THE MARKET




AVERAGE SIZE
AT COMPACTTILT

Low installation height

With a compact design - and low installation height, the machine's inherent breaking forces are preserved and minimize the addition of unnecessary equipment weight.

Unique low weight

All CompactTilt products have a low net weight. At minimum product weight on tilt and tiltrotator, the excavator can effectively utilize its innate lifting capacity and strength excavation work.



Multiple tilt degrees






CompactTilt has 2x50° tilt degrees. With 2x50° degrees of tilt, full flexibility is achieved in the digging arm for versatile solutions construction work.

Open shielding

CompactTilt's products have an open shield. With an open screen, easy access is achieved to cleaning and maintenance of the product in a working environment with stones, gravel and soil.







Price list

Compacttilt™	Description	Quick coupler	The machine must be equipped with		Choice of Hydraulic system	Item no.	Price. EUR Suggested retail price exclusive VAT and shipment.
			1P	1P+LH			
CT1 ^{G1} Excavator weight max 1,2 t 	<ul style="list-style-type: none"> • Semi-automatic • 2x50° • Only 148 mm in width • Weight 15 kg • Incl. 1T Hook 	S30-150 S30-180 MH30	●			CT1	2.450,00
CT2 ^{G3} Excavator weight 1-2 t 	<ul style="list-style-type: none"> • Hydraulic quick coupler • 2x50° tilt degrees • Only 148 mm in width • Weight 30 kg • Pin-lock • Incl. 1T Hook 	Lehnhoff S30-150 S30-180 MH30 Twin hitch system possible		●	HS4 (standard turning block)	CT2-HS4	4.000,00
			●		HS2 (incl. valve integrated on the tilt for easy mounting when the machine doesn't have locking hydraulic)	CT2-HS2	4.600,00
CT3 ^{G2} Excavator weight 2-3 t 	<ul style="list-style-type: none"> • Hydraulic quick coupler • 2x50° tilt degrees • Only 198 mm in width • Weight 48 kg • Pin-lock • Incl. 2T Hook 	S40 Lehnhoff CW05 Twin hitch system possible		●	HS4 (standard turning block)	CT3-HS4	5.670,00
			●		HS2 (incl. valve integrated on the tilt for easy mounting when the machine doesn't have locking hydraulic)	CT3-HS2	6.120,00
CT6 ^{G1} Excavator weight 3-6 t 	<ul style="list-style-type: none"> • Hydraulic quick coupler • 2x50° tilt degrees • Only 198 mm in width • Weight 65 kg • Pin-lock • Incl. 2T Hook 	CW05 CW10 S40 Hydrema Twin hitch system possible		●	HS4 (standard turning block)	CT6-HS4	7.020,00
			●		HS2 (incl. valve integrated on the tilt for easy mounting when the machine doesn't have locking hydraulic)	CT6-HS2	7.570,00
CT10 ^{G2} Excavator weight 6-10 t 	<ul style="list-style-type: none"> • Hydraulic quick coupler • 2x50° tilt degrees • Only 288 mm in width • Weight 95 kg • Pin-lock • Incl. 3T Hook 	CW10 Lehnhoff S45 Hydrema Twin hitch system possible		●	HS4 (standard turning block)	CT10-HS4	8.135,00
			●		HS2 (incl. valve integrated on the tilt for easy mounting when the machine doesn't have locking hydraulic)	CT10-HS2	8.735,00

Designations: The machine must be equipped with:
1P = The machine has 1 proportional outlet
1P+LH = The machine has 1 proportional outlets + locking hydraulics

COMPACTTILT™ ROTATOR™

|| PRICE LIST 2023 ||

Compacttilt™ Rotator	Description	Type of Quick coupler	The machine must be equipped with				Cable set + control box incl.	Choice of Control system	Item no.	Price. EUR Suggested retail price exclusive VAT and shipment.
			1P	2P	2P+LH	3P+LH				
CTR2 Excavator weight up to 2T 	<ul style="list-style-type: none"> • Full rotation • Hydraulic quick coupler • 2x50° • Only 253 mm in width • Weight 65 kg • 1 extra outlet • incl. 1T hook 	S30-150 S30-180 MH30 Twin hitch system possible			●	●	HS8 (8 hoses). The machine is equipped with all necessary hydraulics and electric control for assembly. Delivered without operating system.	CTR2-HS8	9.965,00	
			●	●			HS4 (4 hoses). The most common configuration. Utilizes the tilt hydraulics for quick change and extra outlet.	CTR2-HS4	11.585,00	
			●				HS2 (2 hoses). A Proportional control system. Joystick included.	CTR2-HS2	15.650,00	
CTR3 Excavator weight 2-3T 	<ul style="list-style-type: none"> • Full rotation • Hydraulic quick coupler • 2x50° • Only 285 mm in width • Weight 92 kg • 1 extra outlet • CT-Lock • incl. 1T hook 	S40 Twin hitch system possible			●	●	HS8 (8 hoses). When the machine is equipped with all necessary hydraulics for assembly. Delivered without operating system.	CTR3-HS8	10.500,00	
			●	●			HS4 (4 hoses). The most common configuration. Utilizes tilt the hydraulics for quick-change use and extra outlet.	CTR3-HS4	12.350,00	
			●				HS2 (2 hoses). A proportional control system. Joystick included.	CTR3-HS2	16.100,00	
CTR6 Excavator weight 3-6T 	<ul style="list-style-type: none"> • Full rotation • Hydraulic quick coupler • 2x50° • Width: Only 360 mm w/o. claw 400 mm. w. S40 w. claw 490 mm. w. H45/S45 w. claw • Weight from 175 kg • Extra outlets: 3/8" for S40 1/2" for H45/S45 • incl. 2T hook 	S40, S45, Hydrema Twin hitch system possible			●	●	HS8. (w/o. diverter valve) When there is NO electricity on the tiltrotator. Delivered without control system. Claw is not possible.	CTR6-HS8	15.470,00	
					●	●	HS8. (w. diverter valve) When there is electricity on the tiltrotator. There can be switched between extra outlet and extra outlet for claw. Delivered without control system.	CTR6-HS8-0V	16.000,00	
			●				HS4. (4 hoses) The most common configuration. Utilizes the tilt hydraulics for use quick change and extra outlet and claw.	CTR6-HS4	16.670,00	
			●				HS2. (2 hoses). A proportional control system. Utilizes the tiltrotator's functions at once. Inclusive joystick and touch screen.	CTR6-HS2	21.070,00	
CTR10 Excavator weight 6-10T 	<ul style="list-style-type: none"> • Full rotation • Hydraulic quick coupler • 2x50° • Only 390 mm. w/o. claw 490 mm. w. claw • Weight 280/320 kg • 1 Extra outlet with claw 2 Extra outlets w/o claw • incl. 3T hook 	S45 Hydrema Twin hitch system possible			●	●	HS8 (8 hoses) High Flow When there is NO electricity on the tiltrotator. NOTE: Manual switching between additional outlets and claw. High flow on extra outlet. Delivered without operating system.	CTR10-HS8-HF	17.340,00	
					●	●	HS8 + diverter valve. (8 hoses). When there is NO electricity on the tiltrotator. You can switch between extra outlet and extra outlet for claw. Delivered w/o operation system.	CTR10-HS8-0V	17.870,00	
			●				HS4-HighFlow. (4 hoses) A high flow on extra outlets. Manual switch between extra outlet and claw.	CTR10-HS4-HF	19.070,00	
			●				HS4 (4 hoses) The most common configuration. Utilizes the tilt hydraulics for quick change and extra outlet and claw.	CTR10-HS4	19.070,00	
			●				HS2. (2 hoses) A Proportional control system. Utilizes the tiltrotator's functions at once. Joystick + touch screen included.	CTR10-HS2	23.470,00	

Designations: The machine must be equipped with:
 1P = The machine has 1 Proportional outlet
 2P = The machine has 2 pcs. Proportional withdrawals
 2P+LH = The machine has 2 pcs. Proportional outlets + locking hydraulics

3P+LH = The machine has 3 pcs. Proportional outlets + locking hydraulics
 High Flow = More oil for extra outlet. Kes. If necessary clippers are used.
 Proportional = Roll control

Options


Complete claw incl. hydraulics	CTR6, CTR10	Rotation sensor integrated	All CTR models	Compact-oil	CTR3, CTR6	Compact-oil adapter plate	S40, S45
Price, fitted suggested retail price excl. vat. and shipping	4.950,00 (retrofitting not possible)	Price, excl. VAT. EUR	2.450 (retrofitting not possible)	Price excl. VAT. EUR	950,00	Price excl. VAT. EUR	950,00

Options for HS2 Control System

Track control	Boom swing	Dozer blade	Hand support for joystick	PVM for analog set (box + cable)	Pilot valve kit incl. cable to PVM	Installation of Control System	
						HS2	HS4, HS8
2.850,00	On request	On request	155,00	380,00	900,00	3.400,00	1.850,00




Our DNA is product optimization and development - and we work for creating great machine experiences

Compactilt™ is a 100% tilt and tiltrotator factory, and this means that the factory on Funen exclusively deals with the optimization and production of tilt and tiltrotator products. We look forward to continuing the journey in collaboration with our dealers to create good machine experiences.



Welcome!

Select Department

<p>Sales</p>  <p>Click Here</p>	<p>Installation & Assembly</p>  <p>Click Here</p>	<p>Service & Warranty</p>  <p>Click Here</p>
--	--	---

Dealer Portal

At **Compactilt™** we value communication, good relationships and easy accessibility.

That is why we have created a portal for our dealers, where all updated material is organized and easily accessible - ready when you need it.



Compactilt™ will make newsletters more relevant to you

Once a month we send out a newsletter to our dealers by e-mail. We do it because that you can keep up to date with:

- Product news, development initiatives
- Prices
- Delivery times

Not receiving the email yet? - then send an email to: marketing@compactilt.com

At Compactilt™ we have a phone number for everything - CALL +45 64 42 20 80



DEALER CONTACT

Maria Gade

is responsible for Compactilts dealers.

phone.: +45 23 72 36 74

e-mail: maria@compactilt.com

Orders are sent directly to: sales@compactilt.com

