

# CONGRATULATIONS WITH YOU

# COMPACTTILT™



SEE RECOMMENDATIONS OF FOCUS AREAS



# 3 FOCUS AREAS

THE FULL USER, SERVICE AND DOCUMENTATION GUIDE IS SUPPLIED WITH YOUR PRODUCT. HERE ARE A FEW SELECTED POINTS FROM IT.



## SETTING UP CT PRODUCT (GENERALLY)

- ◆ Warranty registration on CT dealer portal made, with a review of the function test scheme.
- ◆ Rotation speed is set to a minimum of 8 sec
- ◆ Max machine pressure 220 bar.
- ◆ Pay attention to the use of the correct hose dimension.
- ◆ Installation of electricity is carried out in supplied hose bags.



## IN USE

- ◆ Lubrication must be carried out daily / 8th operating hour. (lubricant overview is in the accompanying documentation). \*1  
A Compactilt product cannot be overlubricated.
- ◆ Note: if a leveling bucket is used that is too wide, the tiltrotator can be subjected to overload.
- ◆ Check for kinks/breaks on hoses - this will indicate something has pinched.
- ◆ When replacing hoses - pay attention to the correct use of dimensions.
- ◆ Ensures that shielding is intact - it protects the exposed parts.
- ◆ No use of hydraulic hammer on tiltrotators.
- ◆ Ensure correct use of pallet forks so that unnecessary overloading does not occur. \*2
- ◆ Lifting hook is used by ensuring that shielding is free from lifting straps. \*3



## SERVICE INTERVAL

When carrying out a registered service inspection at 500 hours or 12 months (whichever comes first) +12 months warranty is obtained. Service must be registered and performed by your machine dealer - and let it follow the machine's normal service interval with advantage. The user manual contains a complete overview of instructions for maintenance.

CT Service mark is applied to the machine!  
Contact your machine dealer for an agreement on service.

Tightening torque table for Compactilt products:

Bolt size [mm]	Torque [NM] (10.9 bolts)	Torque [NM] (12.9 bolts)
M5	8,1	9,7
M6	14	17
M8	33	40
M10	65	79
M12	114	136
M14	181	217
M16	277	333

**Warranty Registration**

Date: \_\_\_\_\_

Company/Signature: \_\_\_\_\_

**Service Check**

Date: \_\_\_\_\_

Company/Signature: \_\_\_\_\_

Service must be performed by registered CT dealer. Service performed either yearly or at 500h.

www.compactilt.com

\*1: Grease containing graphite and copper must not be used. It is secured that the grease gun and grease nipples are free for dirt before lubrication is carried out.

\*2: Correct installation of pallet forks

\*3  
Lifting hook

