

|| PRICE LIST 2025 ||

An obvious choice for excavators

in the weight class 0-10 tons



Narrow design

Compacttilt has been developed for working in narrow gutters and is equipped with compacttilt's patented motor a cylinder-free product. It ensures:

- No stamps that can "get stuck"
- Safe view of the work area from the cab
- Dig in narrow trenches and avoid unnecessary soil movement
- Easier access to the work zone which consists of many supplies – eg city zones

WITH CYLINDERS



WITHOUT CYLINDERS



AVERAGE SIZE ON THE MARKET



AVERAGE SIZE AT COMPACTTILT

Low installation height

With a compact design - and low installation height, the machine's inherent breaking forces are preserved and minimize the addition of unnecessary equipment weight.

Unique low weight

All Compacttilt products have a low net weight. At minimum product weight on tilt and tiltrotator, the excavator can effectively utilize its innate lifting capacity and strength excavation work.








Multiple tilt degrees

Compacttilt has 2x50° tilt degrees. With 2x50° degrees of tilt, full flexibility is achieved in the digging arm for versatile solutions construction work.

Open shielding

Compacttilt's products have an open shield. With an open screen, easy access is achieved to cleaning and maintenance of the product in a working environment with stones, gravel and soil.




Compacttilt™	Description	Type of Quick Coupler	The excavator is with		Semi Automatic	Choice of Hydraulic System	Item No.	Price. EUR exclusive VAT and shipment
			AUX1	AUX1+LH				
CT1 Excavator weight max 1,2t. 	<ul style="list-style-type: none"> • 2x50° tilt degrees • From 148 mm in width • Weight from 20 kg • Incl. 1T Hook 	S30-150 S30-180 MH30	●		●	None (Semi Automatic Quick Coupler)	CT1	2.550
				●			HS3 (3 hoses) (Hydraulic Quick Coupler)	CT1-HS3
CT2 Excavator weight 1-2t. 	<ul style="list-style-type: none"> • Hydraulic quick coupler • 2x50° tilt degrees • From 148 mm in width • Weight from 30 kg • Pin-lock • Incl. 1T Hook 	S30-150 S30-180 MH30 CW05		●		HS4 (4 hoses)	CT2-HS4	4.100
			●				HS2 (2 hoses) (Incl. Valve Integrated)	CT2-HS2
CT3 Excavator weight 2-3t. 	<ul style="list-style-type: none"> • Hydraulic quick coupler • 2x50° tilt degrees • From 198 mm in width • Weight from 38 kg • Pin-lock • Incl. 1T Hook 	S40 CW05 HS03		●		HS4 (4 hoses)	CT3-HS4	5.700
			●				HS2 (2 hoses) (Incl. Valve Integrated)	CT3-HS2
CT6 Excavator weight 3-6t. 	<ul style="list-style-type: none"> • Hydraulic quick coupler • 2x50° tilt degrees • From 198 mm in width • Weight from 65 kg • Pin-lock • Incl. 2T Hook 	S40 S45 CW05 CW10 HS03		●		HS4 (4 hoses)	CT6-HS4	7.200
			●				HS2 (2 hoses) (Incl. Valve Integrated)	CT6-HS2
CT10 Excavator weight 6-10t. 	<ul style="list-style-type: none"> • Hydraulic quick coupler • 2x50° tilt degrees • From 288 mm in width • Weight from 95 kg • Pin-lock • Incl. 3T Hook 	S45 CW10		●		HS4 (4 hoses)	CT10-HS4	8.600
			●				HS2 (2 hoses) (Incl. Valve Integrated)	CT10-HS2

Designations: **The excavator is with:**
AUX1 = The excavator has 1 proportional outlet
LH = The excavator has locking hydraulics

COMPACTTILT™ ROTATOR™


|| PRICE LIST 2025 ||

Compacttilt™ Rotator	Description	Type of Quick Coupler	The excavator is with				Cableset + Controlbox Incl.	Choice of Hydraulic System	Item No.	Price. EUR exclusive VAT and shipment	
			AUX1	AUX1 2	AUX1 2+LH	AUX1 2 3+LH					
CTR2 Excavator weight: max 2,2t. 	<ul style="list-style-type: none"> • Infinite rotation • Hydraulic quick coupler • 2x50° tilt degrees • From 253 mm in width • Weight from 68 kg • 1 Extra outlet • Incl. 1T Hook • Incl. CT-Lock 	S30-150 S30-180 MH30 Twin Hitch System Possible				●	HS8 (8 hoses)	CTR2-HS8	10.400		
								●	HS6 (6 hoses)	CTR2-HS6	11.600
				●				●	HS4 (4 hoses)	CTR2-HS4	12.100
			●					●	HS2 (2 hoses) (Incl. Proportional Control System)	CTR2-HS2	17.100

Options

Rotation Sensor: **2.830** HS2 Track Control: **3.230** HS2 Dozer Blade: **1.700** HS2 Hand Support for Joystick: **160**


HS2 Standard Installation: **3.830** HS2 Connection of Joystick Switch: **250**

CTR3 Excavator weight: 2-3t. 	<ul style="list-style-type: none"> • Infinite rotation • Hydraulic quick coupler • 2x50° tilt degrees • From 285 mm in width • Weight from 98 kg • 1 Extra outlet • Incl. 1T Hook • Incl. CT-Lock 	S40 Twin Hitch System Possible				●	HS8 (8 hoses)	CTR3-HS8	10.900		
								●	HS6 (6 hoses)	CTR3-HS6	12.600
				●				●	HS4 (4 hoses)	CTR3-HS4	12.900
			●					●	HS2 (2 hoses) (Incl. Proportional Control System)	CTR3-HS2	18.000

Options

Rotation Sensor: **2.830** CT-Oil (S40): **1.350** CT-Oil Adapter (S40): **600** HS2 Track Control: **3.230** HS2 Dozer Blade: **1.700**

HS2 Hand Support for Joystick: **160** HS2 Standard Installation: **3.830** HS2 Connection of Joystick Switch: **250**


CTR6 Excavator weight: 3-6t. 	<ul style="list-style-type: none"> • Infinite rotation • Hydraulic quick coupler • 2x50° tilt degrees • Width: from 360 mm. w/o. gripper 400 mm. w. S40 w. gripper 490 mm. w. H45 w. gripper 490 mm. w. S45 w. gripper • Weight from 185 kg • Extra Outlet: 3/8" for S40 1/2" for H45/S45 • Incl. 2T Hook • Incl. CT-Lock 	S40 S45 Twin Hitch System Possible				●	HS8 (8 hoses) Without Valve	CTR6-HS8	16.500		
								●	HS8 (8 hoses) With Valve	CTR6-HS8	17.000
				●				●	HS4 (4 hoses)	CTR6-HS4	17.800
			●					●	HS2 (2 hoses) (Incl. Proportional Control System)	CTR6-HS2	23.200

Options

Gripper: **5.250** Rotation Sensor: **2.830** CT-Oil (S40): **1.350** CT-Oil Adapter (S40): **600** HS2 Track Control: **3.230** HS2 Dozer Blade: **1.700**

HS2 Hand Support for Joystick: **160** CT-Oil S45/H45: **1.900** CT-Oil Adapter S45/H45: **950** HS2 Standard Installation: **3.830**

HS2 Connection of Joystick Switch: **250**

CTR10 Excavator weight: 6-10t. 	<ul style="list-style-type: none"> • Infinite rotation • Hydraulic quick coupler • 2x50° tilt degrees • Width: Only 390 mm. w/o. gripper 490 mm. w. gripper • Weight 280/320 kg • 1 Extra Outlet w. gripper 2 Extra Outlet w/o. gripper • Incl. 3T Hook • Incl. CT-Lock 	S45 Twin Hitch System Possible				●	HS8 (8 hoses)	CTR10-HS8	19.100		
								●	HS8 + Valve (8 hoses)	CTR10-HS8-V	19.500
				●				●	HS4 (4 hoses)	CTR10-HS4	20.500
				●				●	HS4 - High Flow (4 hoses)	CTR10-HS4-HF	21.000
			●					●	HS2 (2 hoses) (Incl. Proportional Control System)	CTR10-HS2	25.800

Options

Gripper: **5.250** Rotation Sensor: **2.830** CT-Oil (S45/H45): **1.900** CT-Oil Adapter (S45/H45): **950** HS2 Track Control: **3.230**

HS2 Dozer Blade: **1.700** HS2 Hand Support for Joystick: **160** HS2 Standard Installation: **3.830** HS2 Connection of Joystick Switch: **250**

Designations: The excavator is with:

AUX1 = The excavator has 1 proportional outlet

AUX2 = The excavator has 2 proportional outlet

AUX3 = The excavator has 3 proportional outlet

LH = The excavator has lock hydraulic

High Flow = More oil for extra outlet. For example, if added equipment is to be used.

Proportional = Control System with L8 SWAB Joystick

Note:

CT-Oil is not possible with CTR10 High Flow

CT-Oil (hydraulic tool change) can be added as an option on all configurations (not dependent on HS2)

Rotation Sensor (integration for machine control) can be added as an option on all configurations (not dependent on HS2)

HS2 Standard Installation subject to the machine's configuration. Relocation or connection of switches is not included in the standard setup and must be selected as an option




Our DNA is product optimization and development - and we work for creating great machine experiences

Compacttilt™ is a 100% tilt and tiltrotator factory, and this means that the factory on Funen exclusively deals with the optimization and production of tilt and tiltrotator products. We look forward to continuing the journey in collaboration with our dealers to create good machine experiences.

www

Welcome!

Select Department

Sales	Installation & Assembly	Service & Warranty
		
Click Here	Click Here	Click Here

Dealer Portal

At **Compacttilt™** we value communication, good relationships and easy accessibility.

That is why we have created a portal for our dealers, where all updated material is organized and easily accessible - ready when you need it.

NEWS

Compacttilt™ will make newsletters more relevant to you

Once a month we send out a newsletter to our dealers by e-mail. We do it because that you can keep up to date with:

- Product news, development initiatives
- Prices
- Delivery times

Not receiving the email yet? - then send an email to: marketing@compacttilt.com

At Compacttilt™ we have a phone number for everything - **CALL +45 64 42 20 80**



Palle Andersen
Sales Manager
Telephone.: +45 44 14 19 76
E-Mail: pan@compacttilt.com



Maria Gade
Sales Director
Telephone.: +45 23 72 36 74
E-Mail: maria@compacttilt.com



Orders are sent directly to: sales@compacttilt.com